

Product Data Sheet

ISO Bitumen Varnish A 203

Description:

ISO Bitumen Varnish A 203 is low-viscosity varnish based on a special mixture of bitumen and white spirit. The product can be applied to concrete and steel constructions to give a coating with very good moisture barrier properties. If applied to wooden parts, the low viscosity allows deep penetration and impregnation.

ISO Bitumen Varnish A 203 contains no volatile aromatic or halogenated compounds.

Technical Data:

viscosity	6 - 15 s (DIN 6 beaker)
colour	black (RAL 9005)
composition	bitumen, white spirit and special additives
application methods	dip, spray, brush, pour
cleaning of equipment	use white spirit to clean equipment
warning label	F (flammable)

Storage:

Store in well closed containers in dry and cool areas. Shelf life: more than 2 years.

Processing:

Stir well before use. Use only in well ventilated areas, avoid sparks and open flame.

Please see material safety data sheet for additional information.

This data sheet replaces previous issues.

Edition: 23.11.16

Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and therefore entirely your own responsibility. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you. Of course we will provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.