

Product Data Sheet

Expansion Resin ISO-PUR HS 760/15

Description:

ISO-PUR HS-760/15 is a fast-curing 2-component polyurethane cast resin with excellent mechanical properties. ISO-PUR HS-760/15 fixes and seals pipe penetrations reliably within bricking. The sealed areas are gas-and waterproof and high thermally resistant.

Technical Data:

- Material properties according to VP 601 (DVGW)
- Thermally resistant till 650 °C for 30 minutes*
- Torsion-resistant till 240 Nm*
- No shrinkage
- Fast curing
- Good hydrolysis stability

* measurements by ISO-ELEKTRA

Containers:

ISO-PUR HS-760/15 is delivered in containers with a volume of up to 10 ltr. Delivery in cartridges of 0,6 ltr. is also possible on request. Other packings on request

Storage:

Store dry and well closed.

Processing:

Resin and hardener have to be mixed right before use. To make processing easier, both components are supplied as a kit already in the correct ratio. Mixing should not exceed about 30 seconds, the mixture is then poured into the cavity to be filled and foaming will start.

This data sheet replaces previous issues.

Edition: 17.11.16

Our technical advice - whether verbal, in writing or by way of trials - is given in good faith but without warranty, and this also applies where proprietary rights of third parties are involved. It does not release you from the obligation to test the products supplied by us as to their suitability for the intended processes and uses. The application, use and processing of the products are beyond our control and therefore entirely your own responsibility. Should, in spite of this, liability be established for any damage, it will be limited to the value of the goods delivered by us and used by you. Of course we will provide products of consistent quality within the scope of our General Conditions of Sale and Delivery.